

according to Regulation (EC) No 1907/2006

SCHNEIDÖL SUPERCUT (W394S4)

Revision date: 16.05.2024 Product code: W394S4 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SCHNEIDÖL SUPERCUT (W394S4)

UFI: 66X1-Y0MF-Q00J-HCW3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricants, greases, release products. Metal working fluids. Metal working fluids.

Uses advised against

Do not use in cavities.

1.3. Details of the supplier of the safety data sheet

Company name: WOCKEN Industriepartner GmbH & Co.KG

Street: Industriestr. 14
Place: D-49716 Meppen

Telephone: +49/(0)5931/801-0 Telefax: +49/(0)5931/801-90

E-mail: info@wocken.com

Contact person: Joachim Wolbers Telephone: +49/(0)5931/801-20

E-mail: jwolbers@wocken.com
Internet: www.wocken.com

Responsible Department: Sicherheitsdatenblätter. REACh

1.4. Emergency telephone Information Center against Poisoning (GIZ) Bonn, Phone: 0049/228/19240

<u>number:</u> (24-hour emergency call)

Further Information

Follow the instructions for use on the label. To avoid risks to man and the environment, comply with the instructions for use.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.



according to Regulation (EC) No 1907/2006

SCHNEIDÖL SUPERCUT (W394S4)

Revision date: 16.05.2024 Product code: W394S4 Page 2 of 11

P501 Dispose of contents/container to according to local / regional / national / international

regulations for disposal.

Additional advice on labelling

Classification according to Regulation (EC) No 1272/2008 [CLP] Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H222-H229

Precautionary statements

P210-P211-P251-P410+P412

2.3. Other hazards

Wear suitable protective clothing, gloves and eye/face protection. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Do not breathe aerosol.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous additions:

Relevant ingredients

| CAS No | Chemical name | | | | | |
|------------|---|--------------|------------------|--|--|--|
| | EC No Index No REACH No | | | | | |
| | Classification (Regulation (EC) No 1272/2008) | | | | | |
| 68476-40-4 | Hydrocarbons, C3-4; Petroleum gas (Nota K, <0,1% 1,3-Butadien (EINECS 203-450-8)) | | | | | |
| 270-681-9 | | 649-199-00-1 | 01-2119486557-22 | | | |
| | Flam. Gas 1, Liquefied gas; H220 H280 | | | | | |

Full text of H and EUH statements: see section 16.

Further Information

The labeling of an aspiration hazard (Asp. Tox. 1 H304) is for aerosol dispensers and containers with sealed sprayer not required (Regulation (EC) 1272/2008, Annex 1, 1.3.3).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! In all cases of doubt, or when symptoms persist, seek medical advice. Remove contaminated, saturated clothing immediately. Remove persons to safety. Keep away from unprotected people. Keep upwind. Ventilate affected area.

After inhalation

Provide fresh air. Remove casualty to fresh air and keep warm and at rest. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated clothing immediately and dispose off safely. Wash contaminated clothing before reuse. Seek medical attention if problems persist.



according to Regulation (EC) No 1907/2006

SCHNEIDÖL SUPERCUT (W394S4)

Revision date: 16.05.2024 Product code: W394S4 Page 3 of 11

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eyelids open. Protect the injured eye. Rinse also under the lid of the eyelid. Consult an ophthalmologist.

After ingestion

No usual way of intake because of aerosol.

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical attention if problems persist.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: difficulties of breathing. Headache. Dizziness. Dizziness. Coughing. Nausea.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Dry extinguishing powder. Foam. Water spray jet.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Pressurised container: May burst if heated. Vapours can form explosive mixtures with air. Thermal decomposition can lead to the escape of irritating gases and vapors. In case of fire and/or explosion do not breathe fumes.

In case of fire may be liberated: carbon monoxide (CO). Carbon dioxide (CO2). Organic cracking products.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear chemical resistant suit.

Additional information

Contaminated fire-fighting water must be collected separately. Co-ordinate fire-fighting measures to the fire surroundings.

Use water spray jet to protect personnel and to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Wear personal protection equipment. Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Remove persons to safety. Keep away from unprotected people. Keep upwind.

For emergency responders

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

For containment

Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Take up

Print date: 03.06.2024



Safety Data Sheet

according to Regulation (EC) No 1907/2006

SCHNEIDÖL SUPERCUT (W394S4)

Revision date: 16.05.2024 Product code: W394S4 Page 4 of 11

mechanically, placing in appropriate containers for disposal.

Other information

Ventilate affected area.

6.4. Reference to other sections

Treat the recovered material as prescribed in the section on waste disposal. Disposal: see section 13. Safe handling: see section 7. Personal protection equipment: see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Do not use in cavities. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Pressurised container: May burst if heated. Avoid contact with eyes. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours may form explosive mixtures with air. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material.

Advice on general occupational hygiene

Work in well-ventilated zones or use proper respiratory protection. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work. Take off contaminated clothing and wash it before reuse. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin and eyes.

Further information on handling

Heating causes rise in pressure with risk of bursting.

Remove all sources of ignition.

After use replace the closing cap immediately.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. T < 50 °C

Observe the storage regulations of the TRGS 300 for flammable aerosols.

Hints on joint storage

Note joint storage restrictions of Technical Rules TRGS 509 and TRGS 510.

Further information on storage conditions

Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Lubricants, greases, release products. Metal working fluids. Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

| CAS No | Name of agent | | | | | | | |
|--------------|--|----------------|--------|----------------------|--|--|--|--|
| DNEL type | | Exposure route | Effect | Value | | | | |
| 68476-40-4 | 68476-40-4 Hydrocarbons, C3-4; Petroleum gas (Nota K, <0,1% 1,3-Butadien (EINECS 203-450-8)) | | | | | | | |
| Worker DNEL, | long-term | dermal | 1 ' | 23,4 mg/kg bw/day | | | | |

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

SCHNEIDÖL SUPERCUT (W394S4)

Revision date: 16.05.2024 Product code: W394S4 Page 5 of 11













Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations. Have eye showers and safety shower readv.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. EN 166

Hand protection

Protect skin by using skin protective cream. Tested protective gloves are to be worn: EN ISO 374 The most suitable glove should be chosen in consultation with the glove supplier / manufacturer who can provide information on the breakthrough time of the glove material.

Suitable material: NBR (Nitrile rubber).

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Observe the wear time limits as specified by the manufacturer.

Skin protection

When used as intended no extra body protection is required. Protective clothing: Body protection must be selected depending on the activity and possible impact. EN 13034/6

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protective equipment: Self-contained respirator (breathing apparatus). In principle it's not allowed to use AX-filters against organic substance mixtures.

Thermal hazards

Pressurised container: May burst if heated.

Environmental exposure controls

Leakage into the environment must be prevented. Do not allow uncontrolled leakage of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol

Colour: light yellow, clear
Odour: like: Aerosol propellant.
Odour threshold: not determined

Melting point/freezing point:

Not applicable, aerosol
Boiling point or initial boiling point and

- 42 °C

boiling range:

Flammability: not determined Lower explosion limits: 1,5 vol. % Upper explosion limits: 9,5 vol. % Flash point: < 0 °C Auto-ignition temperature: not determined Decomposition temperature: Not applicable, aerosol Not applicable, aerosol pH-Value: Not applicable, aerosol Viscosity / kinematic:

Print date: 03.06.2024



Safety Data Sheet

according to Regulation (EC) No 1907/2006

SCHNEIDÖL SUPERCUT (W394S4)

Revision date: 16.05.2024 Product code: W394S4 Page 6 of 11

Water solubility: Immiscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

Not applicable, aerosol

Not applicable, aerosol

Density (at 20 °C):

Relative vapour density:

not determined

not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not explosive, but the formation of explosive vapor / air mixtures is possible.

Self-ignition temperature

Solid: not determined Gas: not determined

Oxidizing properties not determined

Other safety characteristics

Evaporation rate: not determined Viscosity / dynamic: Not applicable, aerosol

Further Information

Aerosol, Technical specifications: Internal pressure (20 $^{\circ}$ C) = 0,45 MPa; Internal pressure (50 $^{\circ}$ C) = 0,80 MPa aerosol container: nominal volume = 400 ml; void = 520 ml; Test pressure = 1,5 MPa

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non-reactive under normal use conditions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

10.4. Conditions to avoid

In case of exceeding the storage temperature: >50 °C Danger of bursting container.

Remove all sources of ignition. Ignition hazard. Protect against: heat. UV-radiation/sunlight. frost. Protect from moisture.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

In case of fire may be liberated: carbon monoxide (CO). Carbon dioxide (CO2). Organic cracking products.

Further information

In case of exceeding the storage temperature: >50 °C Danger of bursting container.

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.



according to Regulation (EC) No 1907/2006

SCHNEIDÖL SUPERCUT (W394S4)

Revision date: 16.05.2024 Product code: W394S4 Page 7 of 11

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

The labeling of an aspiration hazard (Asp. Tox. 1 H304) is for aerosol dispensers and containers with sealed sprayer not required (Regulation (EC) 1272/2008, Annex 1, 1.3.3).

11.2. Information on other hazards

Endocrine disrupting properties

No further relevant information available.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Leakage into the environment must be prevented.

| CAS No | Chemical name | | | | | | | | |
|------------|---|---------------|-------|-----------|----------------------------|-----------------|--|--|--|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source | Method | | |
| 68476-40-4 | Hydrocarbons, C3-4; Petroleum gas (Nota K, <0,1% 1,3-Butadien (EINECS 203-450-8)) | | | | | | | | |
| | Acute fish toxicity | LC50 mg/l | 49,47 | | Fish, no other information | Environmental | The Ecosar class program has been develo | | |
| | Acute algae toxicity | ErC50 mg/l | 12,32 | 96 h | algae | Risk Assessment | Calculation using ECOSAR Program v1.00. | | |
| | Acute crustacea toxicity | EC50 mg/l | 69,43 | 48 h | Daphnia sp. | Risk Assessment | Calculation using ECOSAR Program v1.00. | | |

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available



according to Regulation (EC) No 1907/2006

SCHNEIDÖL SUPERCUT (W394S4)

Revision date: 16.05.2024 Product code: W394S4 Page 8 of 11

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|------------|---|---------|
| 68476-40-4 | Hydrocarbons, C3-4; Petroleum gas (Nota K, <0,1% 1,3-Butadien (EINECS 203-450-8)) | 1,09 |

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No further relevant information available.

Further information

Doesn't get into the sewage water as long as the process is carried out according to regulations.

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

slightly hazardous to water (WGK 1)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Consult the appropriate authorities about waste disposal. Dispose of waste according to applicable legislation. Only take completely empty aerosol cans to the recycling collection. Return cans that are not completely empty to the collection point for household chemicals.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

Contaminated packaging

Dispose of waste according to applicable legislation. Completely emptied packings can be re-cycled. Recycle sales packaging via DSD (Duales System Deutschland).

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2





according to Regulation (EC) No 1907/2006

SCHNEIDÖL SUPERCUT (W394S4)

Revision date: 16.05.2024 Product code: W394S4 Page 9 of 11

Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Marine pollutant: Nein

Special Provisions: 63, 190, 277, 327, 344, 381,959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

 14.3. Transport hazard class(es):
 2.1

 14.4. Packing group:

 Hazard label:
 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards



according to Regulation (EC) No 1907/2006

SCHNEIDÖL SUPERCUT (W394S4)

Revision date: 16.05.2024 Product code: W394S4 Page 10 of 11

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning Keep away from sources of ignition - No smoking.

14.7. Maritime transport in bulk according to IMO instruments

No data available

Other applicable information

Transport as "limited quantity" according to chapter 3.4 ADR/RID.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in

paints and varnishes:

Information according to Directive

P3a FLAMMABLE AEROSOLS

2012/18/EU (SEVESO III):

Additional information

REACH Regulation (EC) No 1907/2006, as last amended by Commission Regulation (EU) 2023/2482.

49,3 % (340,17 g/l)

CLP Regulation (EC) No 1272/2008, as last amended by Regulation (EU) 2023/1434.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosol Liquefied gas

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Europäisches

Übereinkommen über die internationale Beförderung gefährlicher Güter auf der Straße) IMDG: International

Maritime Code for Dangerous Goods (Internationaler Seeschifffahrtscode für gefährliche Güter) IATA:

International Air Transport Association (Internationaler Luftverkehrsverband) GHS: Global harmonisiertes

System zur Einstufung und Kennzeichnung von Chemikalien EINECS: Europäisches Verzeichnis der auf dem

Markt vorhandenen chemischen Stoffe ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Tödliche Konzentration, 50% LD50: Tödliche Dosis, 50%

Key literature references and sources for data

Information from our suppliers as well as data from the "Database of registered substances" of the European Chemicals Agency (ECHA) were used for the preparation of this safety data sheet.

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

| Classification | Classification procedure | | | | |
|----------------------|--------------------------|--|--|--|--|
| Aerosol 1; H222-H229 | On basis of test data | | | | |

Relevant H and EUH statements (number and full text)

Print date: 03.06.2024



Safety Data Sheet

according to Regulation (EC) No 1907/2006

SCHNEIDÖL SUPERCUT (W394S4)

Revision date: 16.05.2024 Product code: W394S4 Page 11 of 11

H220 Extremely flammable gas.H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. This information is intended to give you indications for the safe handling of the product mentioned in this safety data sheet during storage, processing, transport and disposal. The details are not transferable to other products. Insofar as the product is mixed with other materials, mixed or processed, or subjected to processing, the information in this safety data sheet, unless expressly stated otherwise, can not be transferred to the new material produced in this way.

Identified uses

| No | Short title | LCS | SU | PC | PROC | ERC | AC | TF | Specification |
|----|--|-----|-------|----|-------|-----|----|----|---------------|
| 1 | Lubricants, greases, release products, | - | 3, 22 | 24 | 7, 11 | - | - | - | Aerosol |
| | Industrial spraying, Non | | | | | | | | |
| | industrial spraying | | | | | | | | |

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

SU: Sectors of use

PROC: Process categories

AC: Article categories

TF: Technical functions

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)